


PLATINA

BP WHITE PRIMER

WATER THINNABLE CEMENT PRIMER



Colour Range



White only

Finish



Matt

Toxicity



VOC - 20 - 25 gm/L

Fire Hazard Class



Non-flammable



Pot Life of Thinned Material
24 hrs

Shelf Life

2 years from the date of
manufacture

Product Description

BP White Primer (WT) is a specially formulated acrylic-based primer that provides long-lasting protective coating for interior walls. It is an air drying primer with low smell and forms a tough, hard film over masonry and asbestos surfaces. It is free from any heavy metals like lead, mercury or chromium.

Recommended Use

Masonry, Asbestos and Brickwork surfaces

Drying Time



SD: 1- 2hrs depending on weather conditions

HD: 4 - 6hrs depending on weather conditions

Coverage



Brush application - 80-100
sq.ft/L/coat

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Dilution



Primer: Water = 1 : 1 (depending on required consistency)

No. of coats required



One (apply 1 extra coat if required)

Recommended Thinner



Potable water

Application Method



Brush/ Roller/ Spray

Consistency



It is a free flowing highly viscous fluid

Flash Point



100% water - based. NA

PLATINA

BP WHITE PRIMER

WATER THINNABLE CEMENT PRIMER



Packs



25 L

Surface Preparation



Ensure the surface is rubbed properly with Sandpaper No. 60/80/100/120 in phases and make sure all dust is removed.

Wipe clean with water and make sure the surface is fully dry.

Directions for Application



Apply 1 coat of BP White Primer (WT) after diluting properly and straining through a clean cloth.

It can be applied by brush or spray. Brushing viscosity should be 50 – 60 sec at 30° C in Ford Cup B4 and in case of spray application it should be 25 -35 sec at 30° C in Ford Cup B4

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Please keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Special Note

Before painting the following things should be checked thoroughly:

1. Moisture content of the wall (ideal condition – below 12%)
2. pH value of the wall surface (ideal condition – between 7 -11)

Version No: BPP1/12/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com