

# PLATINA WEATHERCOAT ALL GUARD

LUXURY EXTERIOR EMULSION



## Colour Range



Over 2,000 shades

## Finish



High Sheen

## Toxicity



VOC - 38.4 gm/lt

## Fire Hazard Class



Non-flammable



Pot Life of Thinned Material  
Overnight

## Warranty \*



## Product Description

WeatherCoat All Guard is a high-performance, premium acrylic exterior emulsion with Silicon enhanced unique chemical composition that protects your wall from the damaging effects of harsh weather conditions. The paint has great water-repellent property, in addition to its polymer composition that prevents dust settling on the walls. The paint also comes with a 8 years warranty and retains a newly painted look for years.

## Recommended Use

Exterior plastered surfaces, asbestos, concrete blocks, fiberboards

## Coverage

60-70 sq.ft/lt/2 coats, under ideal test conditions.  
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

## Recommended Undercoats

**Primer:** For wall/ plastered surfaces – WeatherCoat Exterior Primer / Alternatively, WeatherCoat All Guard diluted using 1 L of water with 1 L of emulsion may be used

**Putty:** For wall/plastered surfaces – Bison Wall Putty

## Recommended Surface

Sand/ cement plaster, asbestos, brickwork, concrete block and fiberboard

## Drying Time



**SD:** 60 min depending on weather conditions

**HD:** 6 - 8 hours

## Gloss Level



10 - 15 at 60° GH when released

## Application Method



Brush / Roller / Spray

## Recommended Thinner



Potable water

## Dilution Ratio



**Brush:** 350 ml of water/1L emulsion  
In case of N Base shades, no dilution is advised to ensure proper colour depth.

## Dilution of dark shades only



Maximum dilution should be 10 - 15 % depending on shade. Coverage may be less compared to light shades.

PLATINA WEATHERCOAT  
**ALL GUARD**  
 LUXURY EXTERIOR EMULSION



## Packs



20 Ltr

## Surface Preparation



**For fresh/new surfaces:** Strip all loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry.



Apply one coat of primer and allow it to dry for 6 – 8 hours.

**For Previously Painted Surfaces:** Strip all the old paint and remove all the loose particles before starting the above process.

## Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

### Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

### Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Version No: BPP1/12/2019. Please note that this data sheet supersedes all previous versions.

## BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
 Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com