

PRODUCT DATA SHEET

Silk Illusions Non-metallic

Silk Illusions Non- metallic is a 100% acrylic emulsion paint for interior application. It is a special effect paint that creates a variety of effects on interior walls in various colours. Different types of designs such as combing, spatula, sponging, weaving etc. can be created using various application tools. The product has been developed to provide slow-drying characteristics so that the designs made out of it get sufficient open time for creation.

Usage Areas:

Interior Puttied/POP/Wooden surfaces

Directions for Application :

Surface Preparation

On Previously Painted Surfaces: Strip all the old paint from the surface and wipe clean. Sand it with emery paper 80/100 and wipe clean. Apply the first coat of primer and let it dry for 6 to 8 hours. Smoothen the surface by applying thin coats of Happy wall putty(No dilution) to fill in all the dents. Let the putty to dry overnight. Sand the surface again, with emery paper 200/220, and wipe clean. Apply the second coat of primer and let it dry for 6 to 8 hours. Sand the surface with emery paper 320 and wipe clean. Apply one coat of illusions Sealer and allow it to dry for 6 hours.

On fresh/New Surfaces: Strip all the loose particles from the surface via wire brushing and scraping and wipe down. Wash the surface with water and let it dry. After this follow the steps recommended for previously painted surfaces.

Note: Use suitable wood primer for application on wood.

Design Application:

Step 1: Apply 2 coats of Silk Luxury Emulsion as base coat in the desired colour. Apply the first coat and let it dry for at least 6 to 8 hours before applying the second coat of Silk. Allow it to dry for at least 6 to 8 hours.

Step 2: Tint Silk Illusions to get the desired shade and use a brush to apply it directly on the previously prepared surface, without dilution. Use the tools specified in the recommended manner to create the design of choice on the wall.

Note: For large wall applications, complete the design in segments.

Technical data :

Drying Time :

Surface dry : 16-20 hours

*Hard dry : Min 48 hours**

*Ensure thorough drying of minimum two weeks before cleaning.

Dilution Ratio:

No dilution for design application.

Points To Note:

- Stir well and strain before use.
 - Do not apply when ambient temperature is below 10⁰ C.
 - Recoat and drying of paint are tested at 30+/-2⁰ C and 60-65% RH. These may vary under different conditions.
 - Fire Hazard Class: Non-Flammable.
 - Tint with Berger Paints colorants only for shades. Colorants addition should be max 4% by volume.
 - Keep the container tightly closed in cool and dry place.
 - Please keep it out of reach of children and away from foodstuff.
 - In case of contact with eyes, wash immediately with water and seek medical advice.
 - For safety measures, refer to MSDS.
-