

PLATINA

RANGOLI TOTAL CARE

PREMIUM INTERIOR ACRYLIC EMULSION



Colour Range



Over 2,000 shades

Finish



Rich matt

Toxicity



VOC - <50 gm/L
Dry film is non-toxic,
lead and arsenic free

Fire Hazard Class



Non-flammable



Pot Life of Thinned Material
Overnight

Product Description

Rangoli Total Care is formulated with special types of co - polymers and fine extenders to give best-in- class coverage and butter -like smooth finish to the walls. Its enhanced bio - resistant formula prevents walls from algae and fungal attacks.

Recommended Use

Sand, cement plaster surface, asbestos, brickwork, concrete block and fiberboard

Coverage

Brush / Roller : 100 - 120 sq.ft/ L /2 coats
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/ plastered surfaces - BP Cement Primer WT (Alkali Resistant)

Putty: For wall/ plastered surfaces - Bison Wall Putty / Happy Wall Putty

Drying Time



SD: 15 - 25 min depending on weather conditions | **HD:** 3 - 4 hours

Application Method



Brush / Roller / Spray

Dilution Ratio



Brush application: 500 ml of water/ 1 L
of emulsion

In case of N base shades, no dilution is advised to ensure proper colour depth.

Recommended Thinner / Cleaner



Potable water

PLATINA

RANGOLI TOTAL CARE

PREMIUM INTERIOR ACRYLIC EMULSION




Packs



20 Ltr

Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.

Apply the first coat of primer and allow it to dry for 6 - 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.

Sand the surface with Emery Paper No. 100 and wipe clean.

Apply the second coat of primer and allow it to dry for 6 - 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.



For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process of primer and putty application.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio - Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Cleaning Instructions

Use only toilet soap to clean stains

Use only a soft white cotton cloth for cleaning

While cleaning, wipe gently without using pressure

Attempt cleaning the surface only after one week of application

Version No: BPP1/12/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
 Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com