



Exterior/Interior under coating Bio-Wash

Product composition Berger Paints Bio-Wash is a unique paint, formulated with high degree of Santroprite, which is Sodium Penta Chlorophenate with some other additives and diluant. It is an excellent product, which kills any type of fungus growth on walls, wood and its by products.

USP It kills all variety of fungus from its roots. It is free from any heavy metals like lead, mercury and chromium.

Surface preparation and application procedure: Sand the surface with sand paper no 50/60 thoroughly. If the fungus attack is severe, use coir brush thoroughly. Wash the surface with potable water nicely, so that all dust and foreign materials is washed off from the surface. Allow the surface to dry fully. Apply Berger Bio-Wash paints as per specified dilution by brush. Allow the paint to penetrate into the surface and let it stay overnight. Next day sand the surface with Water Paper No 150/180 in wet condition so that all killed roots are washed out from the surface. Allow it to dry over night. The surface is ready for the next step.

Special note

| Before painting the following things are to be checked thoroughly | (Ideal condition) |
|---|-------------------|
| (1) Moisture content of the wall | Below 12 % |
| (2) pH value of the wall surface | Below 11 |

If these are violated, it will be at owner's responsibility.

Coverage It can cover 15 to 20 sq.mt. depending on the surface porosity factor.

Recommended dilution Nil. (Max 5% depending on weather condition).

Flash point 100% water base paint, hence NR.

Painting tools Brush

Pot life of thinned material 3 hrs

Shelf life 3 years from the date of manufacturing so long the packet is sealed and kept at normal temperature.

Recommended surfaces Sand/cement plaster, asbestos, Mivan plaster, bricks, etc.

Extra Spl. Note The material must be stirred well before mixing and at every step of application.



Exterior/Interior under coating Bio-Wash

| Do's | Don'ts |
|--|---|
| Mix it well before using the paint. | Apply on a damp wall. |
| Scrape off all old paints thoroughly before painting starts. | Apply on lime wash surfaces. |
| Use soft drinking/municipal water. | Over-thin the putty. |
| Mixing container should be absolutely clean and dry. | Apply paint when ambient temperature is below 10°C. |
| Allow maximum penetration on walls. | Apply paint when temperature is above 45°C. |
| | Use hard water while mixing the paint. |

Packs 5 ltrs, 20 ltrs.

Safety norms Store the product in ambient condition, in a well ventilated store, wear safety goggles, gloves, keep away from children, fire, etc. Avoid eye and skin contact. In case you require, seek medical attention immediately. Wash hand and face with soap and water 2-3 times after painting is over. Use coconut oil on hands and face after washing to get oily skin back. Use mask during application of paint.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 www.bergerpaints.com

CONSUMER RELATIONS MANAGER

Ph: 1800-103-6030, Fax: 91-33-2249-9729/9009, Email: consumerfeedback@bergerindia.com

SMS BERGER to 56767